

Robery Meadows Sub

Line of 25th St. 2500 N

Original post set 1820 by Laughlin with witnesses: 7" sugar N 78 E 6 links; 20" sugar S 59 W 38 links per Marion County Atlas pg. 3. Hosbrook 8-17-1852 called no stone; but, witness 14" beech S 21 F 45 links: 12" back N 88 1/2 w

930

20" sugar S 59 W 38 links per Marion County Atlas pg. 3. Hosbrook 8-17-1852 called no stone; but, witness 14" beech S 21 E 45 links; 12" beech N 88 1/2 W 36 1/2 links per Wayne Township Legal Survey Book pg. 16. Legal Survey distance in Marion/Hendricks counties. Excavated 2-16-95 hub found 8" down. 2.9' S & 2.2' E of PK nail found at surface. Harrison set. Re-tied 5-14-01 by Kiste. Re-tied 8-10-02 by Wilcoxen.

10022004		
REF.	DISTANCE	DESCRIPTION
1.	18.89	Cut 'x' in concrete headwall
2.	47.46	PK nail N PwP#13-451 VB
3.	12.33'	Mag nail w/brass washer S PwP#12-421 VB 8"up
4.	50.94	Mag nail w/brass washer NE PwP#280-421 VB 8"up
		, , , , , , , , , , , , , , , , , , ,